PCT



WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

(11) International Publication Number:

WO 92/03608

D21C 9/02, 9/10

A1

(43) International Publication Date:

5 March 1992 (05.03.92)

(21) International Application Number:

PCT/DK91/00239

(22) International Filing Date:

21 August 1991 (21.08.91)

(30) Priority data:

2034/90

24 August 1990 (24.08.90) DK

(71) Applicant (for all designated States except US): NOVO NORDIŠK A/S [DK/DK]; Novo Alle, DK-2880 Bagsvaerd (DK).

(72) Inventor; and (75) Inventor/Applicant (for US only): PEDERSEN, Lars, Saaby [DK/DK]; Bagsvaerdvej 69B.14, DK-2880 Lyngby (DK).


(74) Agent: NOVO NORDISK A/S; Patent Department, Novo Allé, DK-2880 Bagsvaerd (DK).

(81) Designated States: AT (European patent), BE (European patent), BR, CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FI, FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), NO, SE (European patent) patent), US.

Published

With international search report.

(54) Title: PROCESS FOR TREATMENT OF LIGNOCELLULOSIC PULP AND APPARATUS FOR PERFORMANCE OF THE PROCESS



(57) Abstract


A process for treatment of lignocellulosic pulp comprising a multistage washing of the unbleached kraft brown stock and a xylanase treatment. The xylanase treatment is carried out in a holding tank introduced upstream the first washing unit or downstream one or more of the other washing units except for the last washing unit.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	Pi	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinca	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic	SE	Sweden
CH	Switzerland		of Korca	SN	Senegal
CI	Côta d'Ivoire	KR	Republic of Korea	รบ+	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
cs	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE*	Germany	LU	Luxembourg	US	United States of America
DK	Denmark	MC	Monaco		

⁺ Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.



PROCESS FOR TREATMENT OF LIGNOCELLULOSIC PULP AND APPARATUS FOR PERFORMANCE OF THE PROCESS

1

A common stage in the treatment of wood chips for paper production is chemical pulping, e.g. the so-called kraft process which is an alkaline sulphate 5 cooking of the wood chips. The native wood chips contain around 30% lignin, and at the end of the chemical cooking process less than 5% of the lignin compounds is still left in the pulp. Due to the strong brown color of the remaining lignin and its tendency to darken in UV light or by oxidation this has to be removed in order to obtain a white pulp without the tendency to color reversion.

10 After the sulphate cooking a multistage washing of the unbleached kraft brown stock takes place. The well washed brown stock can then be treated with an enzyme preparation followed by a subsequent wash before entering the bleach plant.

The invention comprises an improvement of this conventional 15 multistage washing of the unbleached kraft brown stock, followed by the enzyme treatment with the subsequent wash, whereby this improvement is a modification, which improves the economy and facilitates the processing.

After a multistage washing of the unbleached kraft brown stock followed by an enzyme treatment with the subsequent wash the brown color can be removed by a multistage bleaching using e.g. chlorine and/or chlorine dioxide. Due to the ever increasing environmental concern, the dosage of chlorine and/or chlorine dioxide has to be kept at a minimum, and it is for that reason that the enzymatic treatment of the kraft cookec pulp has been introduced, vide e.g. The third International Conference on Biotechnology in the Pulp and Paper Industry, 25 Stockholm, 16-19.6, 1986, page 67-69.

Thus, the sequence of the prior art processes in regard to paper pulping is the following:

- 1) kraft cooking of the wood chips,
- 2) multistage washing of the unbleached kraft brown stock
- 3) enzymatic treatment of the washed brown stock
 - 4) bleaching.

The invention comprises the above indicated processes 2) and 3) and is an improvement thereof, as explained in more detail in the following.

Hitherto the multistage washing of the unbleached kraft brown stock has been performed as indicated on the flow sheet of Fig. 1. In addition to the process stages indicated on Fig. 1 an oxygen delignification stage with subsequent washing may be included either before or after the enzyme stage. This prior art process with an enzyme treatment introduced between the cooking and the bleaching sections has some serious drawbacks, e.g. (1) the enzyme stage includes a washing stage, which is a unit operation that represents a large capital investment, and (2) pH adjustment of the pulp may be needed if enzymes with acid pH optimum are used.

Thus, the purpose of the invention is the provision of a process for treatment of lignocellulosic pulp which requires a less expensive apparatus or stated otherwise the provision of a reduction of the price of the prior art method 15 for treatment of lignocellulosic pulp comprising a multistage washing of the unbleached brown kraft stock with subsequent enzyme treatment, washing and bleaching, and a corresponding apparatus for performance of the process.

Now, according to the invention it has been found that the purpose of the invention can be fulfilled, if the enzymatic treatment with the subsequent wash 20 is abandoned altogether and the enzymatic treatment is introduced after one or more of the single washing units in the multistage washings of the unbleached kraft brown stock, or stated otherwise if the enzyme treatment is introduced upstream the prior art position of the enzyme treatment in the multistage washing, in such manner that the multistage washing for washing out of impurities from the 25 kraft cooking and washing out of the residues from the enzyme treatment is combined.

Thus, the process for treatment of lignocellulosic pulp according to the invention comprising a multistage washing of the unbleached kraft brown stock and a xylanase treatment is characterized by the fact that the xylanase treatment is introduced upstream the prior art position of the xylanase treatment in such manner that the stock from the kraft cooking or the washed stock from the outlet side of one or more of the washing units is transported to a holding

ŵ.

;*

tank, that a xylanase with high pH activity and stability and high heat stability is added directly upstream the holding tank, and that the enzyme treated stock is passed further on in the process to the next washing unit. Also in relation to the process according to the invention (Fig. 2) another non-chlorine bleaching stage, e.g. an oxygen delignification stage or an ozone stage may be included either before or after the enzyme stage.

By comparison of Fig. 1 (prior art) and Fig. 2 (invention) it clearly appears that the invention requires one washing unit less than the prior art process, and thus, the process according to the invention fulfils the purpose of 10 the invention. Furthermore, as the tank on Fig. 1 used for the enzyme treatment normally also serves as buffer tank between the kraft cooking and the bleaching plant the residence time of the pulp in the tank often varies within a wide range, e.g. between 30 minutes and 24 hours. In the invention the tank is an integrated part of the washing process. It only serves the need for holding time for the 15 enzyme treatment, which makes it much easier to control the enzyme treatment time. Finally, the invention provides a much better connection to the existing wash water streams. The entire amount of wash water obtained in the process according to the invention will end up in the recovery system for the kraft cooking process, which means that everything that is solubilized during the enzyme 20 treatment will be burned in the recovery boiler whereby the BOD, load from the enzyme stage on the effluent streams is eliminated. This is not the case in the prior art system. In the prior art system the wash water from the washing stage after the enzyme treatment normally has to be sewered. The enzyme treatment according to the invention also releases more cooking chemicals from the pulp 25 than a conventional wash with water. This makes it possible to obtain an even better recovery of cooking chemicals than normally obtained.

The three washing units on Fig. 2 are not limiting to the invention, but just an example. Each single unit can represent more than one washing stage. With three washing units one, two or three enzyme treatment units can be introduced according to the invention; just one enzyme treatment unit is shown on Fig. 2.

4.

к,

ì

The xylanase with high pH activity and stability and with high heat stability, which is used in the process according to the invention, has to show a bleach boosting effect under the conditions present just prior to the last washing unit.

The bleach boosting effect is measured as the kappa number reduction of pulp after an enzyme treatment followed by a C/D-E bleaching compared to a control which is treated in the same way but without addition of enzyme: (Bleach boosting Effect = Kappa number after C/D-E bleaching of enzyme treated pulp minus kappa number after C/D-E bleaching of pulp treated without enzyme).

Also, the invention comprises an apparatus for performance of the process according to the invention. The apparatus according to the invention is characterized by the fact that a holding tank with piping with facilities for introduction of enzyme is introduced upstream the first washing unit or downstream one or more of the other washing units except for the last washing unit, that piping is provided for further transport of the stock to the next washing unit, and that the conventional enzyme treatment unit downstream the washing unit is abandoned.

It is to be understood that at least one holding tank with accessories 20 is introduced, and that the maximum number of holding tanks with accessories, which can be introduced into the sequence according to the invention equals the number of washing units in the multistage washing process.

The following example illustrates the invention in comparison to prior art.

25 EXAMPLE 1

j.

શેલ

In order to illustrate the invention an unbleached and unwashed softwood pulp identified as P was washed in one stage as follows:

The pulp P was diluted with fresh water to a consistency of 1% DS and then reconcentrated to a consistency of approximately 20% on a wire screen.

This washing sequence is the standard washing stage used throughout this example.

After the washing the pH of the pulp was 9.7.

This pulp sample was divided into two halves.

The first half of this one stage washed pulp was xylanase treated under the following conditions without pH adjustment prior to the enzyme addition.

Temperature

70°C

рΗ

9.7

10 Consistency

eter.

10%

Time

3 hours

Xylanase ·

Streptomyces olivochromogenes, vide

Example 6 in WO 91/02839

Enzyme dosage

5000 EXU/kg dry pulp

The definition of the EXU xylanase activity unit appears from AF 293.9/1, obtainable on request from NOVO NORDISK A/S, Novo Allé, DK-2880 Bagsvaerd, Denmark.

The xylanase stage was carried out as follows. The pulp was diluted to the desired consistency by addition of fresh water. The enzyme solution was added and mixed into the pulp by vigorous mixing. The pulp was then placed in a water bath to ensure constant temperature for the remainder of the treatment time. The pulp was not mixed during the three hours of holding time.

After the enzyme stage the pulp was carried through two standard washing stages. This pulp sample which was enzyme treated between the first and the second washing stage, was carried out according to the invention and will be referred to later as inv 1-2.

The second half of the one stage washed pulp was carried through another standard washing stage. After washing the pH of the pulp suspension was 8.7.

This two stage washed pulp was enzyme treated without pH adjustment prior to the enzyme addition under the following conditions:

Temperature

70°C

рΗ

8.7

5

Consistency

10%

Time

3 hours

Enzyme

Streptomyces olivochromogenes, vide

Example 6 in WO 91/02839

Enzyme dosage

2000 EXU/kg dry pulp

The enzyme treatment was carried out as described above.

After the enzyme stage the pulp was carried through one standard washing stage. This sample of pulp, which was enzyme treated between the second and third washing stage, was carried out according to the invention and will be referred to later as inv 2-3.

In order to illustrate the corresponding prior art the pulp P was first carried through three standard washing stages. Then the pH of the pulp was lowered to 6.5 by addition of sulfuric acid and an enzyme stage was carried out under the following conditions.

Temperature

50°C

20

На

6.5

Consistency

10%

Time

3 hours

Enzyme

Pulpzyme™HA

Enzyme dosage

275 FXU/kg dry pulp

The definition of FXU xylanase activity unit appears from AF 293.6/1, obtainable on request from NOVO NORDISK A/S, Novo Allé, DK-2880 Bagsvaerd, Denmark.

The enzyme treatment was made as described above.



joi.

After the enzyme stage the pulp was washed in an extra standard washing stage according to the prior art. This pulp sample will be referred to later as prior.

The above experiment used to illustrate prior art was repeated except 5 that no enzyme was added. This experiment served as a control to demonstrate that the enzyme stage really has an effect on the pulp and will be referred to later as control.

The xylanases used in this example were selected according to their pH optimum in relation to the pH of the pulp.

After enzyme treatments and washings all the pulps were bleached according to the same two stage bleaching sequence (D50 C50) E.

The bleachings were carried out under the following conditions: (D50 C50):

Temperature

Consistency

50°C

15

: 5%

Time

20 minutes

active CI dosage

5.7% (w/w) on dry pulp

E:

Temperature

60°C

20

Consistency

10%

Time

1 hour

NaOH dosage

4.2% (w/w) on dry pulp

After the bleaching the kappa number of all four pulps were determined.

Results

Kappa number of the pulps after the (D50 C50) E bleachings:

	Kappa number	delta Kappa number
		%
5 Control	2.85	· •
Prior	2.52	11.6
inv 1-2	2.50	12.3
inv 2-3	2.31	19.0


It is observed that the kappa number of the enzyme treated pulps are reduced compared to the control. This demonstrates that the enzyme treatment in all three sequences, the prior art and the two inventive sequences, has shown a bleach boosting effect.

It is also seen that the kappa numbers obtained by the two sequences carried out according to the invention are lower than the kappa 15 numbers for the prior art sequence.

This demonstrates that the sequence described by the invention besides giving the technical advantages of avoiding one washing unit gives just as good a kappa number reduction or even a better kappa number reduction as the prior art sequence.

CLAIMS

- 1. Process for treatment of lignocellulosic pulp comprising a multistage washing of the unbleached kraft brown stock and a xylanase treatment, characterized by the fact that the xylanase treatment is introduced upstream the prior art position of the xylanase treatment in such manner that the stock from the kraft cooking or the washed stock from the outlet side of one or more of the washing units is transported to a holding tank, that a xylanase with high pH activity and stability and high heat stability is added directly upstream the holding tank, and that the enzyme treated stock is passed further on in the process to the next washing unit.
- 2. Apparatus for performance of the process according to Claim 1, characterized by the fact that a holding tank with piping with facilities for introduction of enzyme is introduced upstream the first washing unit or downstream one or more of the other washing units except for the last washing unit, that piping is provided for further transport of the stock to the next washing tank, and that the conventional enzyme treatment unit downstream the washing unit is abandoned.






Fig. 2 (The invention)

I. CLAS	SIFICATIO	N OF SUBJECT MATTER (if several class	ification symbols apply, indicate all) ⁸		
According	to Interna	tional Patent Classification (IPC) or to both 9/02, 9/10	National Classification and IPC		
II. FIELD	S SEARCH	ED			
		Minimum Docum	entation Searched ⁷		
Classificati	on System		Classification Symbols		
IPC5		D 21 C		. •	
			er than Minimum Documentation ats are included in Fields Searched ⁸		
SE,DK,F	I,NO c	lasses as above			
III. DOCU		INSIDERED TO BE RELEVANT®			
Category *		on of Document, ¹⁴ with Indication, where a		Relevant to Claim No.13	
Х	29	, 0383999 (ENSO-GUTZEIT (August 1990, see page 1, ne 43)Y) , line 39 -	1	
A	11	ne 45 		2	
х	EP, A2	, 0373107 (SANDOZ AG) 13 e page 6, line 40 - line	June 1990,	1 .	
ΙΔ Ι	26	e page 0, The 40 The	7/	2 ;	
l^				,	
			· · · · · · · · · · · · · · · · · · ·		
			, ; ;		
			· •2		
i					
# Cpaala	l patecori	es of cited documents: ¹⁰	"T" later document published efter	the international filling date	
"A" docu	ment defin	ing the general state of the art which is not e of particular relevance	"T" later document published after or priority date and not in confli- cited to understand the principle invention	ict with the application but e or theory underlying the	
"E" earli filin	e, the claimed invention annot be considered to				
citat	which is cited to establish the publication date of another citation or other special reason (as specified) "Y" document of particular relevance cannot be considered to involve				
othe	r means	ring to an oral disclosure, use, exhibition of	in ine art.	obvious to a person skilled	
		shed prior to the international filing date bu riority date claimed	"&" document member of the same	patent family	
IV. CERTIF		pletion of the International Search	Date of Mailing of this International Sc	earch Report	
29th No			1991 -12- 06	•	
Internationa	l Searching) Authority	Signature of Authorized Officer	<u> </u>	
	CPILLD.	TOU DATENT NEETCE	Marianne Bratsberg	berg	
Form PCT/ISA		ISH PATENT OFFICE nd sheet) (January 1985)	רומו ומוווב טו מנטטבוע		



This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on $\frac{31/10/91}{10}$. The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s) JP-A- 2221482		Publication date
EP-A2- 0383999	90-08-29			
EP-A2- 0373107	90-06-13	CA-A- JP-A-	2003503 2210085	90-05-23 90-08-21

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.